



mm

压入H7座孔内径 Installed Bushing I.D.	外径 O.D.	F	f ₁	f ₂	L ⁰ _{-0.40}													
					15	20	25	30	35	40	50	60	70	80	90			
25 _{+0.052} ₀	28 _{+0.075} _{+0.035}	35	0.8	0.4	2515	2520	2525											
30	34	45				3020	3025	3030										
35	39	50	1.0	0.6		3520	3525	3530	3535									
40 _{+0.062} ₀	44 _{+0.085} _{+0.045}	55					4025	4030	4035	4040								
45	50	60						4530	4535	4540	4550							
50	55	65						5030	5035	5040	5050							
55	60	70						5530	5535	5540	5550							
60	65	75	1.2	0.8				6030	6035	6040	6050	6060						
65 _{+0.074} ₀	70 _{+0.100} _{+0.055}	80						6530	6535	6540	6550	6560						
70	75	85							7035	7040	7050	7060	7070					
75	80	90							7535	7540	7550	7560	7570					
80	85	100							8035	8040	8050	8060	8070	8080				
90	95	110									9050	9060	9070	9080	9090			
100 _{+0.087} ₀	105 _{+0.120} _{+0.070}	120									10050	10060	10070	10080	10090			
110	115	130									11050	11060	11070	11080	11090			
120	125	140									12050	12060	12070	12080	12090			
130	135	155										13060	13070	13080	13090			
140	145	165										14060	14070	14080	14090			
150 _{+0.10} ₀	155 _{+0.170} _{+0.100}	180										15060	15070	15080	15090			
160	165	190										16060	16070	16080	16090			
170	175	200	1.4	0.8								17060	17070	17080	17090			
180	185	215										18060	18070	18080	18090			
190	195	225										19060	19070	19080	19090			
200 _{+0.115} ₀	205 _{+0.210} _{+0.130}	235										20060	20070	20080	20090			
225	230	260										22560	22570	22580	22590			
250	255	290										25060	25070	25080	25090			
265	270	305										26560	26570	26580	26590			
285 _{+0.13} ₀	290 _{+0.260} _{+0.170}	325										28560	28570	28580	28590			
300	305	340										30060	30070	30080	30090			